

R1010

AFFORDABLE MULTIPLE LINE THERMAL INKJET PRINTER



RYNAN Technologies Pte. Ltd.
60 Paya Lebar Road
#10-39 Paya Lebar Square
Singapore 409051
E-mail: info@rynantech.com

R1010 THERMAL INKJET PRINTER

Specifications	
Dimensions (L x W x H)	107.5 x 74.5 x 83 mm 4.23 x 2.93 x 3.27 inch
Weight	450g ~ 0.99 lb
Technology	HP TIJ2.5
Ink security	HP Smartcard
USB 2.0	2 Ports (Keyboard, USB flash)
Build-in sensor	Yes
Mounting brackets	Yes
Anti-Shock	Yes
Material housing	Black anodized aluminum
Interface languages	English (Default), Chinese, Korean, French, German, Spanish, Finnish, Polish, Russian, Portuguese and Vietnamese
Print Performance	
Printability	Text, Logo, Date / Time, Expiry date, Julian date, Counter / Box / Lot, Shift code and Static bar code
Maximum characters	100 characters / messages
Maximum messages length	~ 1 meter
Messages height	2.54 – 12.7 mm
Messages storage	20
Print speed	Max 76 m/min at 300 x 300 dpi
Encoder	Yes
Resolution (DPI)	300x300, 300x150, 300x100
Density	5 levels
Printing distance	1 - 6 mm
Print mode	Continuous, Sensor, Repeat
Print direction	Left to right, Right to left, Left to right mirror, Right to left mirror
Printable surface	Flat, curve (pipe)
Printable material	Porous, Semi-Porous, Non-Porous
Ink Solution	
Ink type	Solvent, Aqueous
Colors	Black, Cyan, Magenta, Green, Red, Blue, Orange, White and Yellow
Ink delivery system	Yes
Operating Environment	
Temperature	5 - 50°C
Power supply	AC 100 - 240V, 50/60Hz, 1.4A, 48W